

CLAIM AMENDMENTS

1.-27. (Cancelled)

28. (Currently Amended) An apparatus comprising:

a weld coupling adapted to be welded to an outer housing of a first cable segment to couple the first cable segment to a second cable segment; and

a ~~thermal insulator~~ thermally insulative material adapted to prevent thermal damage to a communication line of the first cable segment when the weld coupling is welded to the outer housing.

29. (Currently Amended) The apparatus of claim 28, wherein the ~~thermal insulator~~ thermally insulative material contacts the outer housing and contacts the communication line.

30. (Currently Amended) The apparatus of claim 28, further comprising:

an insulating material separate from the ~~thermal insulator~~ thermally insulative material and located between the outer housing and the communication line to protect the communication line, the insulating material being displaced by the ~~thermal insulator~~ thermally insulative material near the weld coupling to prevent thermal damage to the insulating material when the weld coupling is welded to the outer housing.

31. (Currently Amended) The apparatus of claim 30, wherein the insulating material contacts the outer housing and the communication line, and the ~~thermal insulator~~ thermally insulative material contacts the outer housing and the communication line.

32. (Previously Presented) The apparatus of claim 30, wherein the insulating material comprises a polymeric material.

33. (Previously Presented) The apparatus of claim 30, wherein the insulating material transverses an axial length of the first cable segment except where the insulating material is displaced by the thermal insulator.

34. (Currently Amended) The apparatus of claim 30, wherein the ~~thermal insulator~~ thermally insulative material is adapted to prevent at least one of melting and outgasing of the insulating material.

35. (Currently Amended) The apparatus of claim 30, wherein the ~~thermal insulator~~ thermally insulative material is located closer to the weld than to the insulating material.

36. (Previously Presented) The apparatus of claim 28, wherein the weld coupling comprises a sleeve approximately centered where the communication line contacts another communication line of the second cable segment.

37. (Currently Amended) The apparatus of claim 28, further comprising:
~~another a thermal insulator separate from the first thermal insulator and~~ adapted to prevent thermal damage to a communication line of the second cable segment.

38. (Currently Amended) A method comprising:
providing a weld coupling adapted to be welded to a first cable segment and a second cable segment to couple the first and second cable segments together; and
using a ~~thermal insulator~~ thermally insulative material to prevent thermal damage to a communication line of the first cable segment when the weld coupling is welded to at least one of the first cable segment and the second cable segment.

39. (Currently Amended) The method of claim 38, wherein the using comprises:
positioning the ~~thermal insulator~~ thermally insulative material between an outer housing of the first cable segment and the communication line.

40. (Currently Amended) The method of claim 39, wherein the ~~thermal insulator~~ thermally insulative material contacts the outer housing and the communication line.

41. (Previously Presented) The method of claim 39, wherein the outer housing is adapted to be welded to the weld coupling.

42. (Previously Presented) The method of claim 38, further comprising:
preventing damage to a polymeric material that surrounds the communication line when the weld coupling is welded to the outer housing of the first cable segment.

43. (Previously Presented) The method of claim 42, further comprising:
displacing the polymeric material near the weld coupling with another material to prevent thermal damage to the polymeric material.

44. (Previously Presented) The method of claim 38, wherein the using comprises:
preventing thermal damage to the communication line during the formation of a metal weld between the weld coupling and the outer housing of the first cable segment.

45. (Previously Presented) The method of claim 38, further comprising:
preventing thermal damage to a communication line of the second cable segment when the weld coupling is welded to the second cable segment.

46. (Currently Amended) The method of claim 45, wherein the using the ~~thermal insulator~~ thermally insulative material to prevent thermal damage to the communication line of the first cable segment and the preventing of thermal damage to the communication line of the second cable segment comprises:

using separate thermal insulators to protect the communication lines of the first and second segments.

47.-48. (Cancelled)